

EERC Technology - Putting Research into Practice

Mercury Control Technology R&D Program Review

Pittsburgh, PA

July 14–15, 2004

Dennis Laudal, Chad Wocken, and Bob Wiemuth



Evaluation of Mercury Speciation at TXU's Coal-Fired Power Plants *Project Schedule**

- Completion of sampling activities
 - June 2004

- Completion of draft final report
 - August 2004
- Completion of final report
 - November 2004







Acknowledgments

TXU Power: Bob Wiemuth

DOE/NETL: Bob Patton

EERC: Chad Wocken

ADA ES Frontier Geosciences




Martin Lake





Mercury Variability for a Texas Lignite



Project Goal

Establish a comprehensive understanding of mercury speciation, emissions, and removal through existing air pollution control devices for five different TXU plant configurations.



Project Objectives

- Determine speciated mercury emissions at each of the plant configurations.
- Determine mercury removal for each pollution control device (mercury mass balance).
- Determine the effect of blending Texas lignite (TL) and Powder River Basin (PRB) coals on mercury speciation and emissions.



Project Objectives

 Statistically evaluate the variability of coal mercury concentrations.

 Provide guidance and options to TXU in the development of a mercury control strategy.



Plants Tested

THE RES	Coal Type ¹		SO ₂	Particulate
Plant	Blend 1	Blend 2	Control	Control
Big Brown Unit 1	100% PRB	70% TL and 30% PRB	None	ESP and fabric filter ²
Monticello Unit 1	30% TL and 70% PRB	50% TL and 50% PRB	None	ESP and fabric filter ³
Monticello Unit 3	50% TL and 50% PRB	30% TL and 70% PRB	Wet FGD	ESP
Sandow Unit 4	100% TL		Wet FGD	ESP
Martin Lake Unit 3	70% TL and 30% PRB	100% TL	Wet FGD	ESP

¹Coal blend used was for testing purposes only



²ESP and fabric filter in series (COHPAC™ configuration).

³ESP and fabric filter in parallel.


Flue Gas-Sampling Methods

- Ontario Hydro method ASTM D6784-02
 - All sample locations
- CMMs PS Analytical, Tekran, Nippon
 - All locations after the the particulate control device
- EPA Method 324 (Quick CEMs)
 - Stack




Big Brown Unit 1 Sampling

EERC CW23429.CDR






Monticello Unit 1 Sampling





Monticello Unit 3 Sampling


EERC CW23438.CDR






Sandow Unit 4 Sampling

EERC CW23437.CDR





Martin Lake Unit 3 Sampling







Mercury Mass Balance Determinations

 A mercury mass balance will be completed for each pollution control device:

$$Hg_{in} = Hg_{collected} + Hg_{out}$$

 An overall mass balance will also be calculated:

$$Hg_{coal} = Hg_{collected} + Hg_{stack}$$

Where is efficient is each individual pollution control device for removing mercury from the flue gas stream.

Samples Collected

- Coal samples
- ESP hopper ash samples
- Baghouse hopper ash samples
- Wet FGD samples
- Other samples
 - FGD makeup water
 - Pyrite rejects
 - Lime/limestone



Coal Samples

- Mercury
- Chlorine
- Ultimate
- Short proximate

Composite coal samples from the feeders will be collected daily from each unit.

At two of the units, the individual feeders will be analyzed to determine variability in the coal.



ESP and/or Baghouse Samples

- Mercury
- Loss on ignition

Prior to sampling, the ESP and/or baghouse hoppers will be emptied.



Wet FGD Samples

- Percentage solids
- Mercury in liquid per blend
- Mercury in solids

Data to be used to partition mercury in wet FGD samples and to determine mass balances.

